

# COMMAND 200 Series



Give and receive commands with consistent call clarity and stay aware of your environment while multi-tasking. Meet the daily challenges of ATC and C3 situations with robust, lightweight headsets – either single or double sided – for all-day comfort and protection from acoustic injury.

# Key Features

## All-day comfort and robust build

Made from high-quality materials, the CircleFlex™ dual-hinge ear cup system and adjustable headband create a perfect fit

## Protect your hearing with EPOS ActiveGard®

Guards against acoustic injury caused by sudden sound bursts on the line without risk of communication drop-out

## Choose your wearing style

With a flexible microphone boom arm worn on either the left or right

## Multitask with two channel stereo application

Enabling multi-channel communication when switching between air and land-based calls

## Consistent communication with EPOS Voice™ technology

Voice enhancing technology with noise-cancelling microphone delivers clear voice transmission and reception for listeners

---

# Product data

1/3

## General

Contact pressure	1.9 N
Ear coupling	Supra-aural (On Ear)
Cable length	1.0 m / 3.28 ft
Weight of headset	SC 230: 58 g/2.05 oz, SC 260: 86 g/3.04 oz
Storage temperature	-55 °C - +70 °C
Operating temperature	-15 °C - +55 °C
Connector*	Mini-XLR
Weight of headset with cable	SC 230: 69 gr/2.43 oz. SC 260: 97 g/ 3.42 oz
Warranty	2 years

## Mircophone

Microphone type	Electret, noise-cancelling
Sensitivity	-38 dBW/Pa (12.6 mV/Pa) @ 1 KHz, +/- 3 dB
Supply voltage	1-10 V DC
Frequency response	150 - 6,800 Hz

\* SC 260 ATC/C3 UT is unterminated

# Product data

2/3

Product	SC 230 ATC/C3 AG	SC 230 ATC/C3	SC 260 ATC/C3 AG	SC 260 ATC/C3	SC 260 ATC/C3 UT
Art. no.	1000294	1000295	1000292	1000293	1000291
EAN code	57 14708 00095 2	57 14708 00092 1	57 14708 00093 8	57 14708 00094 5	57 14708 00096 9
UPC code	8 40064 40095 4	8 40064 40092 3	8 40064 40093 0	8 40064 40094 7	8 40064 40096 1
Wearing style	SC 230: Headband with side-support.		SC 260: Headband		
<b>Headphones</b>					
<b>Sound pressure level:</b>					
dB SPL @ 1 KHz, 0.5 V	103*	103	103*	103	103
dB SPL @ 1 KHz, 1 mW	88	88	86.5	86.5	86.5
dB SPL @ 1 KHz, 1V	95,5	95,5	99,5	99,5	99,5
Max SPL	103 dB	114 dB	113 dB	114 dB	114 dB
THD, total harmonic distortion	<1 % at 102 dB SPL at 1 kHz	<1 % at 102 dB SPL at 1 kHz	<1 % at 102 dB SPL at 1 kHz	<1 % at 102 dB SPL at 1 kHz	<1 % at 102 dB SPL at 1 kHz
Frequency response	50 – 18,000 Hz	50 – 18,000 Hz	50 – 18,000 Hz	50 – 18,000 Hz	50 – 18,000 Hz
Impedance	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω

# Product data

3/3

## Connector pin\*\*:

Product	SC 260/SC 660 Series	SC 230/SC 630 Series	SC 260 ATC/C3 UT
Pin 1	Mic GND	Mic GND	Shield
Pin 2	Mic +	Mic +	Red
Pin 3	SPK R***	Not connected in headset	Green
Pin 4	SPK L***	SPK L***	Black
Pin 5	SPK GND	SPK GND	White

\* Limited by EPOS ActiveGard®

\*\* Seen from front of mini-XLR

\*\*\* L = mic boom arm side, R = opposite mic boom arm side

## Product

COMMAND 200 Series

## What's in the box

Headset, leatherette ear pads, mounted on headset, cable/clothing clip, mounted, nylon carry pouch

# Spare parts

1/1

Product	Art. no.	Description	EAN code	UPC code
HZP 30 SC 200	1000790	SC 200 Foam Earpads	5714708005919	840064405911
HZP 31 SC 200	1000791	Leatherette Earpads for SC 200	5714708005926	840064405928
PS 01	1000783	Popshield 1 pc	5714708005841	840064405843
HPH 01	1000778	Hygiene cover (10 pcs)	5714708005797	840064405799
HPH 02	1000779	Hygiene cover (50 pcs)	5714708005803	840064405805